

Powered by Android

PAX E700 is a professional integrated terminal device that delve straight into the business demand of operator, it provides omni-channel payments and smart management platform, at same time integrates peripheral value-added applications and services to

help boost business. The E700 is ideally suited for restaurants, hotels, supermarkets, entertainment complex, specialty stores, theme parks and cinemas.





FEATURES & BENEFITS

Flexible Platform

- Abundant Peripheral Ports Enable Creative Management
- Auto Adjusted Brightness Based on Ambient Lighting
- Marketing Aided by Wi-Fi Probe & Bluetooth iBeacon
- Automatic Paper Cutter, Faster Transactions
- Camera Reads 1D / 2D Codes

Security& Reliability

- Prevent Audio Analysis, Ensuring Transaction Safety
- Physical Buttons Endure More Than 1 Million Clicks
- Operates 15 Minutes Minimum Solely on Battery
- Designed with Concealed Screws and Buckles
- Minimum 50,000 Hours of Display Lifespan







OS	PayDroid Powered by Android 7.1
Processor	Quad-core Cortex-A53, 1.8GHz
Memory	2GB DDR + 16GB eMMC 1 x Micro SD Card Slot, Supports up to 128GB
Payment Module	Magnetic Card Reader Smart Card Reader Contactless Card Reader 4.3-inch Color Touchscreen
Camera	0.3 Megapixel Fixed Focus Front Camera 2 Megapixel Fixed Focus Rear Camera Reads 1D & 2D Codes
Fingerprint	Login (optional)
Display	12.5-inch All Perspective IPS Display I FHD 1920 x 1080 pixels Capacitive Touchscreen
Audio	2 x Speakers
Physical Buttons	1 x ON/OFF Key 1 x Printer Paper Button 1 x Volume +/- Key
Communications	Wi-Fi (2.4G / 5G)Supports Probe and Hotspot I 4G (TD-LTE / FDD-LTE) + 3G (WCDMA / CDMA2000) Bluetooth 4.2 Supports iBeacon LAN (10 / 100M)
Card Slots	1 x SIM
Peripheral Ports	4 x type-A USB 1 x type-C USB 1 x RJ11 (24V), Cash Box 1 x RJ45 (LAN) 1 x RJ45 (RS232) 1 x Audio Jack 1 x Charging Port
Printer	3-inch Thermal Printer Print Speed: 150 mm/s Paper Width: 80 mm Paper Diameter: 80 mm Automatic Paper Receipt Cutter
Battery	3.7V / 2200mAH Rechargeable Li-ion Battery
Adapter	Input: 100 - 240V AC, 50Hz / 60Hz Output: 24V DC, 1.5A
Indicators	1 x Printer Indicator: Green (Normal State) Yellow (Out of Paper Indicator) Red Flashing (Error State Indicator)
Physical	L x W x H (mm): 310.8 x 308.9 x 138.8 Weight (kg): 2.1 (including battery)
Environmental	0°C ~ 50°C (32°F ~ 122°F) Operating Temperature -20°C ~ 70°C (-4°F ~ 158°F) Storage Temperature 5% ~ 96% Relative Humidity, Non-condensing
Certifications	PCI PTS 5.x, SRED EMV L1 & L2 EMV Contactless L1 MasterCard Contactless Visa payWave American ExpressPay Discover D-PAS MasterCard TQM FCC Interac_Flash_L2 J/Speedy PTCRB CSEC APCA ABECS UL CE IC





